

MENARDS®

2020 SPRING & SUMMER
OUTDOOR POWER EQUIPMENT



BRUSHLESS 80VOLT MAX



CONTENTS



| | |
|------------------|-------|
| Maintenance | 4 |
| Masterforce® | 5 |
| Engines | 6-7 |
| Lawn Mowers | 8-15 |
| String Trimmers | 16-23 |
| Hedge Trimmers | 24-29 |
| Leaf Blowers | 30-37 |
| Chainsaws | 38-45 |
| Pressure Washers | 46-51 |
| Generators | 52-57 |
| Chore Performers | 58-67 |



PROTECT YOUR POWER

When you pull up to a gasoline filling station, you may start to see some changes. Make sure you look before you pump – the gas you put in your car may no longer be safe for small engines, UTVs and outdoor power equipment.

To learn more, visit: **LookBeforeYouPump.com**

E0-E10 YES!

Fuel containing less than 10 percent ethanol is what you want to look for to keep your equipment running smoothly.

E15-E85 NO

Do not use any fuel containing greater than 10 percent ethanol (E10) in this equipment. It may cause damage or failure and is prohibited by Federal Law.

USE E10 OR LESS

OPEI is the Outdoor Power Equipment Institute.



LAWN CARE TIPS

Fertilizing your lawn

Start your lawn on a regular fertilizing schedule early in the season for better, more consistent results.

Times to cut

Don't cut your lawn when it is wet. That makes it more susceptible to diseases and fungus.

Vacations

If you will be leaving on vacation or other extended absence, try to cut right before you leave.

Debris

Pick up debris in the yard before mowing. This includes rocks, toys, twigs, and small branches.

Grass height

A good height to cut grass down to is 2.5 inches. Try to cut it when it is 4 inches tall.

Protect your eyes

Always wear safety glasses while using outdoor power equipment. Thrown objects can cause serious injury to the eyes.

How to handle clippings

Side discharge tall, overgrown grass to help prevent the mower from bogging down. Mulch clippings to return nutrients to the lawn, and bag them when you want a clean, manicured look.

Plan ahead

Avoid discharging clippings toward roads and sidewalks or against a wall or obstruction, which may cause rocks or other materials to ricochet back towards you.

Maintenance

Extend the life of your engine by performing regular maintenance. It prevents engine hard starts, engine failure and costly repairs. Refer to your engine operator's manual for specific maintenance information.

Check and change your oil

Important to performance, oil lubricates and cools engine parts subject to friction and heat. Check oil level before each use, and change it every 50 hours (walk mowers) or 100 hours (ride mowers) of use or annually, whichever comes first.

Replace your spark plug

A damaged or worn spark plug can decrease fuel efficiency and power output. Replace it every 100 hours or annually, whichever comes first.

Examine your blades

Each season, check for dull or worn mower blades, which can tear, not cut, the blades or grass, making them susceptible to disease.

Check and change your air filter

A dirty air filter affects power and fuel efficiency. Check it monthly and replace it annually. In dusty conditions or when debris is present, clean often.

Fill your can, treat your fuel

Choose a fuel with the least amount of ethanol (alcohol). Gas begins to degrade in as little as 30 days. Add fuel treatment to fresh fuel in your gas can to keep fuel fresh and to prevent engine hard starts.

Prepare before storage

Never leave regular fuel in your mower when storing it. Empty or run the old fuel out first, then add fresh fuel with fuel stabilizer. Leaving old fuel in the mower can create a varnish that will ruin the carburetor.

MASTERFORCE®



80VOLT MAX BRUSHLESS

CRAFTSMAN® ENGINES

AN ENGINE IS ONLY AS TOUGH AS ITS PARTS.

- CRAFTSMAN® engines are constructed with heavy-duty, high-quality parts and a smarter design to provide serious power you can count on
- All CRAFTSMAN® engines come with a 2-year warranty and are backed by a full-service network

CRAFTSMAN®



140cc OHV WALK-BEHIND ENGINE

Overhead Valve Design with Cross-flow Cylinder Head

More efficient, cleaner burning engine. Results in more power and reduces fuel consumption

Aluminum Cylinder Bore

Automotive style piston and rings riding in an aluminum cylinder provides consistent shape, low emissions and low oil consumption

Mechanical Governor

Provides precise control of engine speed and responds 30% faster to sudden load increases than traditional air vane designs

Electronic Ignition

Capacitor discharge ignition provides higher ignition voltage required for easy, dependable starting with no maintenance

CRAFTSMAN® gas-powered engines are designed to perform in harsh conditions and use heavy-duty parts that wear better and last longer. So you get a tough, high-quality engine for your yard care equipment.

- Get more power from the CRAFTSMAN® overhead valve design than similarly sized engines but with fewer emissions
- Hardworking performance ensured by a forged steel crankshaft and ball bearings
- Lasting protection from the wear-resistant, cast-iron cylinder sleeve
- A powerful engine with a much quieter valve train, resulting from the cast-iron camshaft
- Smoother pull starts require less effort due to the mechanical compression release
- Precise and smooth engine speed as a result of the mechanical governor
- Easier, faster maintenance with an extended oil fill and dipstick
- Adjust speed and power to match the job with the ergonomic throttle control

BRIGGS & STRATTON® ENGINES



PROVIDING THE POWER TO ACHIEVE.

- #1 preferred engine among consumers¹
- With over 100 years of American engine expertise, Briggs & Stratton® innovations make engines effortless to use and maintain
- Available on Brute®, Jonsered®, and Poulan Pro® walk-behind mowers; Brute® tillers and log splitters; and Briggs & Stratton® pressure washers



550E Series™



550EX Series™



675EXi 725EXi Series™



550E SERIES™

5.50 ft-lbs Gross Torque* (140cc)

- Prime N' Pull™ starting system for quick, easy starts
- Compact, lightweight and economical design for dependable power
- Less vibration for more user comfort and enhanced engine life

550EX SERIES™

5.50 ft-lbs Gross Torque* (140cc)

- ReadyStart® Starting System with no prime, no choke, no worries – just pull for power; Backed by the Briggs & Stratton Starting Promise™ to start within two pulls or we'll fix it for free**
- Less vibration for more user comfort and enhanced engine life

675EXi-725EXi SERIES™

6.75, 7.25 ft-lbs Gross Torque* (163cc)

- ReadyStart® Starting System with no prime, no choke, no worries – just pull for power; Backed by the Briggs & Stratton Starting Promise™ to start within two pulls or we'll fix it for free**
- Never change the oil, Just Check & Add™†
- Lightest in its class for easy maneuvering
- Tool-less access for easier and quicker regular maintenance

*All power levels are stated Gross Torque at 2600 RPM per SAE J1940 as rated by Briggs & Stratton. These walk mower and pressure washer engines are made in the U.S.A. of U.S. and global parts.

**For more details, visit briggsandstratton.com/na/en_us/support/starting-promise.html

†Regular scheduled maintenance must be performed. To learn more, go to www.justcheckandadd.com or see complete details in the Operating Manual.

Briggs & Stratton's warranty terms and conditions apply. Just Check & Add does not extend the warranty period.

¹Powerpulse® 2017

See <http://www.briggsandstratton.com/us/en/support/warranty> for details.

LAWN MOWERS

CHOOSING THE RIGHT LAWN MOWER THAT MEETS YOUR NEEDS.

Engines

Engine size will depend on what you need a mower to do, whether it's powering through grass, disposing of clippings or, if equipped, operating the transmission. The mower you select will be equipped with the right size engine to live up to the task.

- Briggs & Stratton® has focused on building powerful, tough and innovative engines that are easy to maintain for over 110 years.
- Yard Machines® and Remington® POWERMORE® engines provide serious power you can count on every day.
- The KOHLER® engine, featured on the Jonsered® and Lawn-Boy® walk-behind mower is tough and reliable.

Understanding torque and cc

The power of a walk mower engine is measured in torque and cubic centimeters (cc). Torque is the work power generated by the engine that turns the blade on your mower. The more torque, the more power to cut through high, thick grass.

Engine displacement (or size) is identified in cubic centimeters or cc. It is a measurement of the volume of the fuel and air mixture an engine consumes in each cycle.

So, when looking at the power of an engine, consider both the cc and the torque. Generally, with comparable engine designs, the larger an engine's displacement and the higher the torque rating, the more powerful it is.

What's so great about OHV

Just like automobiles, lawn mower engines with overhead valves (OHV) generally operate more efficiently with fewer emissions. They burn less fuel and offer substantially more power and longer life than comparable non-OHV engines.

What about electric mowers?

Environmentally friendly electric mowers can be corded or battery powered. Both create no emissions, require no gas, and are quieter and lightweight.



PUSH OR SELF-PROPELLED? HOW DO I KNOW?

Push Mowers

If you have a relatively flat yard up to 1/2 acre and prefer to push your mower for exercise, a push mower is ideal for you.

Self-Propelled Mowers

For yards up to 1 acre, a self-propelled mower cuts the grass and powers a drivetrain that propels the mower forward, making it easier and requires less effort.

- All-wheel drive mowers deliver the extra traction needed to take on any type of terrain, even hills. The 4x4 drive system uses a unique single-belt design that drives both the front and rear wheels for the ultimate power.
- Front-wheel drive mowers offer easier maneuverability around trees and flower beds and are ideal for flatter terrain.



LAWN MOWERS



Manual



Electric



Battery



Gas



Self-Propelled

EARTHWISE

EARTHWISE

LawnMaster
TAKE BACK THE YARD

CRAFTSMAN



16" Reel Mower

20" Reel Mower

**18" 10 AMP 2-IN-1
Electric Push Mower**

**20" 13 AMP 3-IN-1
Electric Push Mower**

| | | | | |
|-------------------------------------|--------------------------------|--------------------------------|--------------------------|----------------------------------|
| Menards® SKU | 270-1424 | 270-1426 | 270-1102 | 270-1142 |
| Model | 1816-16EW | 2002-20EW | ME1018X | CMEMW213 |
| Motor / Engine | Manual | Manual | 10 AMP | 13 AMP |
| Engine Torque Power | N/A | N/A | N/A | N/A |
| Mulch / Bag / Side Discharge | Rear | Rear (Includes Grass Catcher) | Mulch / Side Discharge | Mulch / Bag / Side Discharge |
| Starting System | Push Manual | Push Manual | Electric | Electric |
| Deck | 16" Wide | 20" Wide | 18" Plastic | 20" Steel |
| Height System | Quick Snap Height Adjust 1"-3" | Quick Snap Height Adjust 1"-3" | Single Lever | Single Lever Control, 6 Settings |
| Wheels | 10" with 6" Trailing | 10" with 6" Trailing | 6.75" Front / 6.75" Rear | 8" Front / 10" Rear |
| Assembly | Tool-less Assembly | Tool-less Assembly | Minimal | Minimal |
| Warranty | 2-Year Limited | 2-Year Limited | 2-Year Limited | 3-Year Limited |
| Replacement Parts | | | | |
| Blade | N/A | N/A | RMB1018X | 270-4510 |

SUNJOE®**greenworks®****SNAPPER® HD****SNAPPER® HD****14" 24V Cordless
Push Mower****20" 40V Cordless
Push Mower****20" 48V MAX* Cordless
Push Mower****20" 48V MAX* Cordless
Self-Propelled Mower**

| | | | | |
|-------------------------------------|------------------------------|---|--|--|
| Menards® SKU | 270-1147 | 270-1144 | 270-3848 | 270-3849 |
| Model | 24V-MJ14C | 2516302ME | 1687966 | 1688022 |
| Motor / Engine | 24V Brushless Motor | 40V Brushless Motor | 48V Brushless Motor | 48V Brushless Motor |
| Engine Torque Power | 600 Watt | 800 Watts | 800 Watts | 800 Watts |
| Mulch / Bag / Side Discharge | Bag Discharge – 10.6 Gal | Mulch / Bag / Side Discharge | Mulch / Bag / Side-Discharge | Mulch / Bag / Side-Discharge |
| Starting System | Push Button | Push Button | Push Button | Push Button |
| Deck | 14" Poly | 20" Steel | 20" Steel | 20" Steel |
| Height System | 3 Positions (1.18" to 2.52") | Single Lever Height Adjust, 7 Positions | Single Point Height Adjust, 7 Positions | Single Point Height Adjust, 7 Positions |
| Wheels | 5.5" Front / 5.5" Rear | 8" Front / 10" Rear | 8" Front / 10" Rear | 8" Front / 10" Rear |
| Assembly | Minimal | Minimal | Minimal | Minimal |
| Warranty | 2-Year Full | 3-Year Limited | 3-Year Limited Product** 2-Year Limited Battery** | 3-Year Limited Product** 2-Year Limited Battery** |
| Replacement Parts | | | | |
| Blade | MJ401C-BLD | 29172 | 84001939 | 84001939 |
| Battery | 24VBAT – XR 5AH Battery | 267-3318 – 4AH Battery | 1697090 – 5.0 Battery | 1697090 – 5.0 Battery |
| Charger | 24VCHRG – QC – Rapid Charger | 267-3311 – Quick Charger | 1697092 – Charger | 1697092 – Charger |

*Maximum initial battery voltage (measured without workload) is 48-volts. Nominal voltage is 43.

**Visit www.snapper.com for complete warranty details.

As rated by the manufacturer. Color and model may vary.

LAWN MOWERS



Manual



Electric



Battery



Gas



Self-Propelled



21" 80V Cordless Self-Propelled Mower

20" Push Gas Mower

20" 2-IN-1 Push Gas Mower

21" 3-IN-1 Push Gas Mower

| | | | | |
|------------------------------|---|---------------------|---------------------------|------------------------------|
| Menards® SKU | 270-1145 | 270-3817 | 270-3838 | 270-3852 |
| Model | 2500194ME | PTG1220DB | PTG12205B | BSG1221B5 |
| Motor / Engine | 80V Brushless Motor | Ducar® | Ducar® | Briggs & Stratton® |
| Engine Torque Power | Equivalent Torque of 160cc Gas Engine | 150cc 4-Stroke | 150cc 4-Stroke | 140cc 4-Stroke |
| Mulch / Bag / Side Discharge | Mulch / Bag / Side Discharge | Side Discharge | Mulch / Side Discharge | Mulch / Bag / Side Discharge |
| Starting System | Push Button | Recoil Start | Recoil Start | Recoil Start |
| Deck | 21" Steel | 21" Steel | 21" Steel | 22" Steel |
| Height System | Single Lever Height Adjust, 7 Positions | Manual, 3 Positions | Single Lever, 6 Positions | Single Lever, 7 Positions |
| Wheels | 8" Front / 10" Rear | 7" Front / 7" Rear | 7" Front / 11" Rear | 8" Front / 10" Rear |
| Assembly | Minimal | Minimal | Minimal | Minimal |
| Warranty | 4-Year Limited | 1-Year Limited | 2-Year Limited | 2-Year Limited |
| Replacement Parts | | | | |
| Blade | 2903402 | 602007 | 602007 | N/A |
| Battery | 267-3316 – 4AH Battery | N/A | N/A | N/A |
| Charger | 267-3314 – Rapid Charger | N/A | N/A | N/A |
| Oil | N/A | 10W30 | 10W30 | SAE30 / Synthetic 5W30 |
| Air Filter | N/A | 5132 | 5132 | 270-4426 |
| Spark Plug | N/A | 97108 | 97108 | 270-4322 / 270-4432 |

**The gross torque of the engine was laboratory rated at 2800 RPM per SAE J1940 by Kohler®
As rated by the manufacturer. Color and model may vary.

CRAFTSMAN®
**21" 3-IN-1
Push Gas Mower**
CRAFTSMAN®
**21" 3-IN-1
Self-Propelled Gas Mower**
LAWN-BOY®
**21" 3-IN-1 Rear Wheel Drive
Self-Propelled Gas Mower**
CRAFTSMAN®
**21" 3-IN-1
Self-Propelled Gas Mower**

| | | | | |
|-------------------------------------|-------------------------------|-------------------------------|---|-------------------------------|
| Menards® SKU | 270-3840 | 270-3855 | 270-3834 | 270-3841 |
| Model | M105 | M205 | 17732 | M215 |
| Motor / Engine | CRAFTSMAN® | CRAFTSMAN® | Kohler® | CRAFTSMAN® |
| Engine Torque Power | 140cc OHV | 140cc OHV | 149cc XTX | 159cc OHV |
| Mulch / Bag / Side Discharge | Mulch / Bag / Side Discharge | Mulch / Bag / Side Discharge | Mulch / Bag / Side Discharge Ready | Mulch / Bag / Side Discharge |
| Starting System | Auto Choke | Auto Choke | Pull | Auto Choke |
| Deck | 21" Steel | 21" Steel | 21" Steel | 21" Steel |
| Height System | Dual lever, 6 Height Settings | Dual lever, 6 Height Settings | 2-Point Height of Cut 6-Positions 1 ^{1/4"} –3 ^{3/4"} | Dual Lever, 6 Height Settings |
| Wheels | 7" Front / 8" Rear | 8" Front / 8" Rear | 7" Front / 8" Rear | 8" Front / 11" Rear |
| Assembly | Minimal | Minimal | Minimal | Minimal |
| Warranty | 2-Year Limited | 2-Year Limited | 3-Year Engine 2-Year Full | 2-Year Limited |
| Replacement Parts | | | | |
| Blade | CMXGZAM100067 | CMXGZAM100067 | 133-8182-03P / 270-5027 | CMXGZAM100067 |
| Oil | 10W30 | 10W30 | 89885 / 2614259 | 10W30 |
| Air Filter | 490-200-M055 | CMXGZAM200065 | 14 083 22-S | CMXGZAM200065 |
| Spark Plug | CMXGZAM250014 | CMXGZAM250014 | 490-250-K016 | CMXGZAM250014 |
| Drive Belt | | CMGXAM501005 | N/A | CMXGZAM501005 |

*All power levels are stated gross torque at 2600 RPM per SAE J1940 as rated by Briggs & Stratton®
As rated by the manufacturer. Color and model may vary.

LAWN MOWERS



Manual



Electric



Battery



Gas



Self-Propelled

BRUTE



CRAFTSMAN



CRAFTSMAN



CRAFTSMAN



**21" 3-IN-1
Self-Propelled Gas Mower**

**21" 3-IN-1 Rear Wheel Drive
Self-Propelled Gas Mower**

**21" Self-Propelled
Gas Mower**

**23" 3-IN-1 Rear Wheel Drive
Self-Propelled Gas Mower**

| | | | | |
|------------------------------|--------------------------------------|-------------------------------------|-------------------------------|-------------------------------|
| Menards® SKU | 270-3854 | 270-3856 | 270-3842 | 270-3858 |
| Model | BSG1221SEB6 | M310 | M275 | M355 |
| Motor / Engine | Briggs & Stratton® | Briggs & Stratton® | CRAFTSMAN® | CRAFTSMAN® |
| Engine Torque Power | 150cc 4-Stroke | 163cc OHV | 159cc OHV | 196cc OHV |
| Mulch / Bag / Side Discharge | Mulch / Bag / Side Discharge | Mulch / Bag / Side Discharge | Mulch / Bag / Side-Discharge | Mulch / Bag / Side Discharge |
| Starting System | Briggs & Stratton® Electric In Start | One-Step Starting–No Priming Needed | Li-Ion Electric Start | Auto Choke |
| Deck | 22" Steel | 21" Steel | 21" Steel | 23" Steel |
| Height System | Single Lever, 7 Positions | Dual lever, 6 Height Settings | Dual Lever, 6 Height Settings | Dual Lever, 6 Height Settings |
| Wheels | 8" Front / 10" Rear | 8" Front / 11" Rear | 8" Front / 11" Rear | 8" Front / 8" Rear |
| Assembly | Minimal | Minimal | Minimal | Minimal |
| Warranty | 2-Year Limited | 2-Year Limited | 2-Year Limited | 2-Year Limited |

Replacement Parts

| | | | | |
|------------|------------------------|------------------------|---------------|---------------|
| Blade | N/A | CMXGZAM100067 | CMXGZAM100067 | CMXGZAM100067 |
| Oil | SAE30 / Synthetic 5W30 | SAE30 / Synthetic 5W30 | 10W30 | 10W30 |
| Air Filter | 270-4426 | 270-4426 | CMXGZAM200065 | CMXGZAM200065 |
| Spark Plug | 270-4322 / 270-4432 | 270-4322 / 270-4432 | CMXGZAM250014 | CMXGZAM250014 |
| Drive Belt | N/A | CMGXAM501005 | CMGXAM501005 | CMGXAM501005 |

*20V MAX battery, maximum initial battery voltage (measured without a workload) is 20V nominal voltage is 18.
As rated by the manufacturer. Color and model may vary.



Prevent Fuel Problems. Fill Your Can, Treat Your Fuel.

Gasoline begins to go stale in just 30 days, clogging your engine's fuel system with gum and varnish. In addition, ethanol-blended fuels can lead to engine corrosion. Protect your engine by treating clean, fresh fuel. Every time you fill your gas can, add a fuel treatment.

For more information visit: keepfuelfresh.com

STA-BIL 360° Protection™ Ethanol Treatment & Fuel Stabilizer

STA-BIL 360° Performance® is the ultimate fuel additive and is the only additive you need to keep your small engine running strong. Use it every time you fill your gas can to prevent ethanol damage and stabilize your fuel for quick easy starts all season long.

- Prevents ethanol damage
- Stabilizes fuel for 12 months
- Prevents fuel system corrosion
- Removes water caused by ethanol
- Cleans fuel system
- Prevents gum and varnish



STRING TRIMMERS



FIVE EASY WAYS TO MAINTAIN YOUR TRIMMER

- Keep a spare, pre-wound spool on hand for quick replacement.
- Always use the specific line size for your trimmer. Heavier line will stress the motor and gearbox if they weren't designed to handle it.
- Fresh line works best. Old line can crack and break too easily in the middle of a job.
- Keep the trimmer head clean and free of loose objects.
- Always use fresh gas and the proper mixture ratio in your 2-cycle trimmer.

CHOOSING THE STRING TRIMMER THAT MEETS YOUR NEEDS.

Three Types of Power

- 2-cycle engine. The standard for years, these are less expensive and very efficient, with plenty of power to do the job. However, they require mixing oil and gas.
- 4-cycle engine. More power and torque at lower RPMs, these are more fuel efficient with fewer emissions, quieter and do not require mixing oil and gas.
- Electric / Battery. Environmentally friendly, these are powered by either a plug-in cord or a rechargeable battery. They are quieter and lighter weight, but often less powerful.

Two Types of Shafts

- Straight shafts are made for better weight balance and are used by more pros due to their longer reach and cutting head options. These work best for trimming under branches, porches and hedges.
- Curved shafts are generally lightweight, well-balanced and economically priced.

Two Types of Cutting Heads

- Bump head. You simply tap the head to advance the line, then refill and rewind the line as needed.
- Auto-feed. Line automatically advances, then refill the line as needed.
- Fixed line. For easy line changes, simply advance the line and reload in seconds, with nothing to take apart or wind.

NOTE: Consult your owner's manual for the manufacturer's suggested line diameter.

STRING TRIMMERS



Electric



Battery



Gas

EARTHWISE

greenworks

**BLACK+
DECKER**

TORO











**10" 2.6 AMP Corded
String Trimmer**

**13" 4 AMP Corded
String Trimmer / Edger**

**14" 6.5 AMP Corded
String Trimmer / Edger**

**8" 12V Cordless
String Trimmer**

| | | | | |
|----------------------------|------------------|---|---|---------------------------------|
| Menards® SKU | 267-3151 | 267-4909 | 267-3395 | 267-3100 |
| Model | ST00010 | 21212 | BESTA510 | 51467 |
| Motor / Engine | 2.6 AMP | 4 AMP | 6.5 AMP | 12V Battery |
| Cut Width | 10" Cutting Path | 13" Cutting Swath | 14" Cutting Swath | 8" Cutting Swath |
| Shaft | Solid | Straight Telescopic; Rotates for Edging | Straight, Telescopic | Straight, Non-Telescopic, Solid |
| Starting System | Electric | Electric | Electric | Electric |
| Line Size | 0.065" | 0.065" | 0.065" | 0.065" |
| Line Release / Replacement | Bump Feed | Dual Line, Automatic | Single Line, Automatic Feed System | Bump Feed |
| Attachment Capable | No | No | No | No |
| Warranty | 2-Year Limited | 3-Year Limited | 2-Year Limited | 2-Year Full |
| Replacement Parts | | | | |
| Spool (Line) | RS90109 | 29242 – 3 pk Dual Line Auto | 267-3340 (AF-100-3ZP) / 267-3338 (AF-100) | 88185 / 267-3106 |

| |   |   |   |   |
|----------------------------|--|--|--|--|
| | 10" 20V Cordless String Trimmer / Edger | 10" 20V Cordless String Trimmer / Edger | 12" 20V Cordless String Trimmer / Edger | 12" 20V Cordless String Trimmer / Edger |
| Menards® SKU | 267-3252 | 267-3326 | 267-3281 | 267-3292 |
| Model | LST201 | WG154 | LST320C | WG163 |
| Motor / Engine | 20V MAX* Lithium Battery | 20V MAX* Lithium Battery | 20V MAX* Lithium Battery | 20V MAX* Lithium Battery |
| Cut Width | 10" Cutting Swath | 10" to 12" Cutting Swath | 12" Cutting Swath | 12" Cutting Swath |
| Shaft | Straight, Telescopic | Straight | Straight, Telescopic | Straight, Telescopic |
| Starting System | Cordless | Cordless | Cordless | Cordless |
| Line Size | 0.065" | 0.065" | 0.065" | 0.065" |
| Line Release / Replacement | Single Line, Automatic Feed | Single Line, Automatic Feed | Single Line, Automatic Feed | Push Button, Command Feed Spool System |
| Attachment Capable | No | No | No | No |
| Warranty | 2-Year Limited | 3-Year Limited; 1-Year Battery | 2-Year Limited | 3-Year Limited; 1-Year Battery |
| Replacement Parts | | | | |
| Spool (Line) | 267-3340 (AF-100-3ZP) / 267-3338 (AF-100) | 267-3332 | 267-3340 (AF-100-3ZP) / 267-3338 (AF-100) | 267-3332 |
| Battery | 20V – 236-6532 | 20V – 236-4900 | 20V – 236-6532 | 20V – 236-4900 |
| Charger | 236-6534 | 236-4910 | 236-6534 | 236-4910 |
| Replacement Spring | 267-3262 (RC-100-P) | N/A | 267-3262 (RC-100-P) | N/A |

*Battery manufacturer rating = 40V maximum & 36V typical usage. Actual voltage varies with load. As rated by the manufacturer.
Color and model may vary.

STRING TRIMMERS



Electric



Battery



Gas

CRAFTSMAN

MASTERFORCE

BLACK+DECKER

greenworks



**13" 20V MAX*
Cordless String Trimmer**

**12" 20V Cordless String
Trimmer (Tool-Only)**

**13" 40V MAX* Cordless String
Trimmer / Edger**

**15" 40V Cordless
String Trimmer**

| | | | | |
|-------------------------------|------------------------------------|--------------------------|---|------------------------------------|
| Menards® SKU | 267-3182 | 267-3293 | 267-3282 | 267-3078 |
| Model | CMCST900D1 | 4812.1 | LST140C B+D | 2111802ME |
| Motor / Engine | 20V MAX* Lithium-Ion Battery | 20V Brushless Motor | 40V MAX* Lithium-Ion Battery | 40V Torque Drive Motor |
| Cut Width | 13" Cutting Swath | 12" Cutting Swath | 13" Cutting Swath | 15" Cutting Swath |
| Shaft | Straight, Telescopic | Straight, Folded | Straight, Telescopic | Straight |
| Starting System | Cordless | Cordless | Cordless | Trigger Start |
| Line Size | 0.065" | 0.08" Twisted Nylon Line | 0.065" | 0.08" |
| Line Release / Replacement | Single Line, Automatic Feed System | Dual Line, Bump Feed | Single Line, Automatic Feed System | Dual Line, Bump Feed |
| Attachment Capable | No | No | No | No |
| Warranty | 3-Year Limited | 3-Year Limited | 3-Year Limited | 3-Year Limited |
| Replacement Parts | | | | |
| Spool (Line) | 267-3355 (CMZST065) | 267-3335 | 267-3340 (AF-100-3ZP) / 267-3338 (AF-100) | 267-4830 – 0.08" Replacement Spool |
| Battery | 20V – 236-0123 | 252-8030 | 40V – 267-3259 | 267-3317 – 2.5AH Battery |
| Charger | 252-8037 | 252-8037 | 267-3246 | 267-3311 – Quick Charger |
| Replacement Spring | 267-3357 (CMZST120SC) | N/A | 267-3262 (RC-100-P) | N/A |

As rated by the manufacturer. Color and model may vary.

*Battery manufacturer rating = 40V maximum & 36V typical usage. Actual voltage varies with load.










| | 13" 48V MAX Cordless String Trimmer* | 16" 80V Cordless Attachment Capable String Trimmer | 16" 25cc 2-Cycle Curved Shaft Gas Trimmer | 16" 25cc 2-Cycle Straight Shaft Gas Trimmer |
|----------------------------|--|--|---|---|
| Menards® SKU | 267-3308 | 267-3199 | 267-1881 | 267-1882 |
| Model | 1687970 | 2100194ME | Y2510 | Y2560 |
| Motor / Engine | 48V MAX* Lithium-ion Battery | 80V Brushless Motor | 25cc 2-Cycle | 25cc 2-Cycle |
| Cut Width | 13" Cutting Swath | 16" Cutting Swath | 16" Cutting Swath | 16" Cutting Swath |
| Shaft | Straight | Straight | Curved | Straight |
| Starting System | Trigger Start | Trigger Start | Recoil Pull Start | Recoil Pull Start; EX Pull Spring Assist |
| Line Size | 0.08" | 0.08" | 0.095" | 0.095" |
| Line Release / Replacement | Click-N-Trim, Bump Head | Bump Feed / EZ Load Head | Dual Line, Bump Head | Dual Line, Bump Head |
| Attachment Capable | No | Yes | No | No |
| Warranty | 3-Year Limited Product, 2-Year Limited Battery** | 4-Year Limited | 2-Year Limited | 2-Year Limited |
| Replacement Parts | | | | |
| Spool (Line) | 0.08" | 0.08" | 267-6173 (3095L) | 267-6173 (3095L) |
| Oil / Battery | 169-7088 – 2.0 Battery | 267-3313 – 2.0AH Battery | 2-Cycle | 2-Cycle |
| Spark Plug / Charger | 169-7092 – Charger | 267-3314 – Rapid Charger | 270-4341 (49MB2SPP953) | 270-4341 (49MB2SPP953) |
| Bump Knob | 8400-1698 – Bump Feed String Head | N/A | 49MA066P953 | 49MA066P953 |
| Replacement Spring | 0.08" | N/A | 49M0317P953 | 49M0317P953 |

*Maximum initial battery voltage (measured without workload) is 48-volts. Nominal voltage is 43.

**Visit www.snapper.com for complete warranty details.

As rated by the manufacturer. Color and model may vary.

STRING TRIMMERS



Electric



Battery



Gas

CRAFTSMAN®



CRAFTSMAN®



LawnMaster
NOPULL



CRAFTSMAN®



**17" 25cc Curved Shaft
Gas Trimmer**

**17" 25cc Straight Shaft
Gas Trimmer**

**17" 26cc 2-Cycle Straight Shaft
NOPULL™ Gas String Trimmer**

**17" 30cc 4-Cycle Straight
Shaft Gas Trimmer**

| | | | | |
|---------------------------------------|----------------------|----------------------|----------------------------------|-------------------------|
| Menards® SKU | 267-1897 | 267-1898 | 267-1901 | 267-1902 |
| Model | WC215 | WS215 | NPTGSP2617A | WS405 |
| Motor / Engine | 25cc 2-Cycle | 25cc 2-Cycle | 26cc 2-Cycle | 29cc 4-Cycle |
| Cut Width | 17" Cutting Swath | 17" Cutting Swath | 17" Cutting Swath | 17" Cutting Swath |
| Shaft | Curved | Straight | Straight | Straight |
| Starting System | Easy 3-Step | Easy 3-Step | NOPULL™ Electric Push-Start | Advanced 2-Step |
| Line Size | 0.095" | 0.095" | 0.095" | 0.095" |
| Line Release / Replacement | Twisted, 2-IN-1 Head | Twisted, 2-IN-1 Head | Rapid Reload Dual Line Bump Feed | Click-n-Trim, Bump Head |
| Attachment Capable | Yes | Yes | Yes | Yes |
| Warranty | 2-Year Limited | 2-Year Limited | 3-Year Limited | 2-Year Limited |
| Replacement Parts | | | | |
| Spool (Line) | CMXGZAM010044 | CMXGZAM010044 | 0.095" | CMXGZAM010044 |
| Oil | 2-Cycle | 2-Cycle | 2-Cycle | 4-Cycle |
| Spark Plug | 49MA2SPP793 | 49MA2SPP793 | 270-4341 | 49MA2SPP793 |
| Bump Knob | 731-09582-49 | 731-09582-49 | LawnMaster #RR0100 | 731-10783-49 |
| Replacement Spring | 1845 | 1845 | LawnMaster #321001129 | 1845 |

As rated by the manufacturer. Color and model may vary.



HEDGE TRIMMERS



CHOOSING THE RIGHT EXTENSION CORD FOR YOUR OUTDOOR EQUIPMENT

- Match your cord to the work environment, whether indoor or outdoor. Outdoor-rated cords have durable covers to protect from weather and damage.
- Make sure the number of prongs (two or three) fits the outlet you'll be using.
- Get a cord that meets the AMPerage requirements of the tool you're using. Read the owner's manual for assistance. Keep the cord's gauge in mind for maximum output. The lower the gauge number, the more power the cord delivers.
- More isn't better with cord length. The longer the cord, the less power is delivered to the item you're powering. Keep both gauge and length in mind when selecting a power cord.

IN ADDITION TO CLIPPING SHRUBS AND BUSHES, HEDGE TRIMMERS GIVE YOU THE ABILITY TO PRUNE PERENNIALS, GRASSES AND GROUND COVER

Hedge Trimmer Basics

Dual blades cut in either direction from either side of the plant. Blade sizes range from as small as 6.3 inches for an electric detail trimmer to 22-inch blades for heavy-duty cutting. Most blades cut branches up to 3 / 8 inches. The large trimmers can handle branches as large as 1.25 inches. A hand guard is provided for safety.

Weight and balance are very important since you'll be holding the machine at chest height or higher. At times, you'll also be using the tool with your arms extended.

Power

Hedge trimmers are powered by either electricity or gasoline. Base your purchasing decision on how much portability, cutting capacity and power you need.

Electric models are lighter, quieter and vibrate less than gas units. An electric motor drives blades, so there's no need to mix fuel or refill. Smaller yards are especially good candidates for electric trimmers. There are two types:

- Corded models provide constant power as long as you have access to an electrical outlet. The attached cord limits mobility so this may not be the best choice for a lawn with lots of trees. Look for a cord retention system to prevent the cord from being accidentally unplugged during use.
- Rechargeable / battery-operated hedge trimmers and edgers are good alternatives for smaller areas or jobs. They're limited by their run time, and they may not be able to cut larger shrubs as well as a gasoline-powered trimmer.

Gas models use a two-cycle engine, requiring the user to mix oil and gasoline. Mobility and work output are increased with gas trimmers and edgers. However, they're louder and heavier than electric models.

HEDGE TRIMMERS



Electric



Battery



Gas

EARTHWISE

**BLACK+
DECKER**

greenworks

TORO



**18" 3.2 AMP Corded
Hedge Trimmer**

**17" 3.2 AMP Corded
Hedge Trimmer**

**22" 4 AMP Corded
Hedge Trimmer**

**22" 4 AMP Corded
Hedge Trimmer**

| | | | | |
|-------------------|----------------|----------------|----------------|----------------|
| Menards® SKU | 267-4814 | 267-1532 | 267-4927 | 267-4803 |
| Model | HT10218 | BEHT150 | 2200102 | 51490 |
| Motor / Engine | 3.2 AMP | 3.2 AMP | 4 AMP | 4 AMP |
| Blade Length | 18" | 17" | 22" | 22" |
| Starting System | Electric | Electric | Electric | Electric |
| Cordless / Corded | Corded | Corded | Corded | Corded |
| Warranty | 2-Year Limited | 2-Year Limited | 3-Year Limited | 2-Year Limited |

As rated by the manufacturer. Color and model may vary.

EARTHWISE
MASTERFORCE
**BLACK+
DECKER**
CRAFTSMAN

**6-1/4" 3.6V Cordless
Hedge Trimmer**
**22" 20V Cordless
Hedge Trimmer (Tool-Only)**
**18" 20V MAX* Cordless
Hedge Trimmer**
**20V MAX* 22" Cordless
Hedge Trimmer**

| | | | | |
|---------------------------|-------------------------|-------------------------------|------------------------------|------------------------------|
| Menards® SKU | 267-3168 | 267-1530 | 267-1601 | 267-3181 |
| Model | LSS10163 | 4211.1 | LHT218C1 | CMCHTS820D1 |
| Motor / Engine | 3.6V | 20V Flexpower Lithium Battery | 20V MAX* Lithium-Ion Battery | 20V MAX* Lithium-Ion Battery |
| Blade Length | 6.3" Hedge, 3.15" Grass | 22" | 18" | 22" |
| Starting System | Cordless | Electric | Cordless | Cordless |
| Cordless / Corded | Cordless | Cordless | Cordless | Cordless |
| Run Time (Minutes) | Up to 55 Minutes | Up to 90 Minutes | Up to 30 minutes per charge | Up to 30 minutes per charge |
| Warranty | 2-Year Limited | 3-Year Limited | 2-Year Limited | 3-Year Limited |

As rated by the manufacturer. Color and model may vary.

*Battery manufacturer rating = 40V maximum & 36V typical usage. Actual voltage varies with load.

HEDGE TRIMMERS



Electric



Battery



Gas



greenworks®



| | 22" 40V MAX* Cordless Hedge Trimmer | 24" 40V Cordless Hedge Trimmer (Tool-Only) | 24" 80V Cordless Hedge Trimmer (Tool-Only) | 22" 26cc Gas Hedge Trimmer |
|--------------------|-------------------------------------|--|--|----------------------------|
| Menards® SKU | 267-1525 | 267-1542 | 267-1543 | 267-4703 |
| Model | LHT2240C B+D | 2207902ME | 2200094ME | CMXGHBD7186 |
| Motor / Engine | 40V MAX* Lithium-Ion Battery | 40V Motor | 80V Brushless Motor | 26cc |
| Blade Length | 22" | 24" | 24" | 22" |
| Starting System | Cordless | Trigger Start | Trigger Start | Recoil |
| Cordless / Corded | Cordless | Cordless | Cordless | Gas (no cord) |
| Run Time (Minutes) | Up to 30 minutes per charge | Up to 60 Minutes | Up to 60 Minutes | N/A |
| Warranty | 3-Year Limited | 3-Year Limited | 4-Year Limited | 3-Year |

As rated by the manufacturer. Color and model may vary.

SAFETY TIPS WHEN USING YOUR HEDGE TRIMMER

- Keep hands away from blade. Contact with blade will result in serious personal injury.
- Use both hands when operating the hedge trimmer. Using one hand could cause loss of control and result in serious personal injury.
- Keep all parts of the body away from the cutter blade. Do not remove cut material or hold material to be cut when blades are moving. Make sure the switch is off when clearing jammed material. Blades coast after turn off.
- Carry the hedge trimmer by the handle with the cutter blade stopped.
- Hold the power tool by insulated gripping surfaces only because the cutter blade may contact hidden wiring.
- Check the hedge for foreign objects, e.g. wire fences.

LEAF BLOWERS





COMPARING MPH AND CFM

The MPH or miles per hour designation reflects the speed at which air exits the machine. The higher the number, the faster the air is traveling. The higher MPH-rated units provide effective cleaning for smaller, more confined areas.

A more significant rating is CFM or cubic feet per minute. The higher the number, the more air is being moved. The higher CFM-rated units indicate blowers that will effectively clear debris in large areas.

CHOOSING THE RIGHT BLOWER FOR YOUR NEEDS

Gas Blowers

A gas-powered blower gives you maximum mobility and convenience without the limitations of electrical cords. If you have a larger yard to clear and will be working far from electrical outlets, a gas-powered model will offer better performance and higher air power ratings.

Electric Blowers

These units are lightweight, quiet and start instantly for quick cleanup without mixing or adding gas and oil. If you have a smaller area to clear and will be working near a power source, an electric hand-held unit is ideal.

Cordless Blowers

Cordless blowers have good mobility. High-volume batteries provide power and run time, but add weight. Batteries periodically need recharging, so depending on the size of your landscape, you may want to have a spare battery available.

Blower Vacs

3-in-1 blowers, also called blower vacs, perform three functions: blowing, vacuuming and mulching, reducing 8 to 12 bags to a single bag.

LEAF BLOWERS



Electric



Battery



Gas

TORO

WORX

BLACK+DECKER

TORO



7 AMP Power Sweep Electric Leaf Blower

7.5 AMP Electric Leaf Blower

12 AMP Electric Blower / Vac / Mulcher

12 AMP Ultra Electric Leaf Blower / Vac

| | | | | |
|----------------|---|--|--|---|
| Menards® SKU | 267-3115 | 267-2953 | 267-2932 | 267-3125 |
| Model | 51585 | WG506 | BV3600 | 51619 |
| Motor / Engine | 7 AMP Electric | 7.5 AMP Electric | 12 AMP Electric | 12 AMP Electric |
| MPH / CFM | 160 MPH / 155 CFM | 160 CFM | Up to 230 MPH / Up to 385 CFM | 260 MPH / 340 CFM |
| Capacity | N/A | N/A | 10:1 Mulch Ratio / 1.5 Bushels | Up to 88% of Debris Reduced to < 1 / 2" ¹ |
| Impeller | Plastic | | Plastic | Metal |
| Speed Control | 2-Speed | 2-Speed | 2-Speed Switch | Variable Speed |
| Features | Lightweight and easy-to-use; Only 4.7lbs | Lightweight and easy-to-use; Ergonomic grip handle design; Simple tool free assembly; Hassle-free cord retainer | Tool-free change between blower and vacuum; 10:1 mulch ratio; Plastic impeller; includes leaf blaster attachment and concentrator attachment | Blower, vacuum, mulcher with no-tool quick release latch; power insert, concentrator nozzles, bottom-zip vac bag and tubes |
| Weight | 4.7 lbs. | 4.4 lbs. | 8.1 lbs. | 8.5 lbs. |
| Warranty | 2-Year Limited | 3-Year Limited | 2-Year Limited | 2-Year Limited |

As rated by the manufacturer. Color and model may vary.

¹ For comparison purposes only, performance claims based on controlled laboratory testing, debris reduction varies with material type and its condition.

*Battery manufacturing rating = 40V maximum & 36V typical usage. Actual voltage varies with load.

**BLACK+
DECKER****CRAFTSMAN****WORX****MASTERFORCE**

| | 20V MAX* Cordless Leaf Blower | 20V Axial Cordless Leaf Blower | 20V Turbine Cordless Leaf Blower | 20V Cordless Leaf Blower (Tool-Only) |
|-----------------------|---|---|--|---|
| Menards® SKU | 267-3138 | 267-3198 | 267-3134 | 267-3122 |
| Model | LSW221 | CMCBL700D1 | WG547.1 | 4707.1 |
| Motor / Engine | 20V MAX* Lithium-Ion Battery | 20V MAX* Lithium-Ion | 20V MAX* Lithium-Ion Battery | 20V Brushless Motor |
| MPH / CFM | 130 MPH / 100 CFM | 90 MPH / 340 CFM | 55-75 MPH / 270-360 CFM | 100 MPH / 400 CFM |
| Capacity | N/A | N/A | N/A | 20V |
| Impeller | N/A | N/A | N/A | Plastic |
| Speed Control | 1-Speed | Variable Speed | 2-Speed | Variable |
| Features | Lightweight at 3.7 lbs.; Includes battery and charger; Built-in scraper | Axial fan design delivers maximum efficiency and 340 CFM and 90 MPH; Dual speed for control over power and runtime; Debris scraper to loosen stubborn debris; Lightweight design less than 6 lbs for decreased user fatigue | (2) 20V Li-Ion batteries for longer run time; high capacity air volume with turbine fan technology (360 CFM) | Brushless motor; variable speed; turbine fan; good balance and lightweight design; removable tube |
| Weight | 3.7 lbs. | 5.9 lbs. | 4.4 lbs. | 4 lbs. 10 oz. |
| Warranty | 2-Year Limited | 3-Year Limited | 3-Year Limited | 3-Year Limited |

As rated by the manufacturer. Color and model may vary.

*Battery manufacturing rating = 40V maximum & 36V typical usage. Actual voltage varies with load.

LEAF BLOWERS



Electric



Battery



Gas



greenworks®



| | 40V MAX* Cordless Leaf Blower | 40V Jet Cordless Leaf Blower | 48V MAX* Cordless Leaf Blower | 80V Jet Cordless Leaf Blower |
|----------------|---|--|---|---|
| Menards® SKU | 267-3135 | 267-3103 | 267-3118 | 267-3119 |
| Model | LSW40C | 2411902ME | 1687968 | 2400094ME |
| Motor / Engine | 40V MAX* Lithium-Ion Battery | 40V Brushed Motor | 48V MAX* Brushed Motor | 80V Brushless Motor |
| MPH / CFM | Up to 100 MPH | 125 MPH / 450 CFM | Up to 120 MPH** / Up to 450 CFM | 145 MPH / 580 CFM |
| Capacity | N/A | N/A | 48V MAX* | N/A |
| Impeller | N/A | N/A | 3.25" | N/A |
| Speed Control | 1-Speed | Variable Speed Trigger, Cruise Control, Turbo | Infinite Speed Control | Variable Speed Trigger, 3-Speed Settings |
| Features | Lightweight at 4 lbs.; Includes battery and charger; Built-in scraper | Delivers gas-like power with 125 MPH / 450 CFM power. Variable speed trigger and cruise control for easy use. Turbo button for max power. Up to 30 minute runtime with included 2.5AH battery fully charged. Battery charges in 75 minutes with Quick Charger. | Up to 450 CFM / 120 MPH**, Up to 20 minutes of run time with 2.0 battery on low**, Boost mode button, Infinite speed control, Compatible with Briggs & Stratton® 48V MAX* 2.0 and 5.0 batteries | Delivers 32cc gas-like power with 145 MPH / 580 CFM power. Variable speed trigger, 3-speed settings. Up to 30 minute runtime with included 2.0AH battery fully charged (267-3313). Battery charges in 30 minutes with Rapid Charger (267-3314). |
| Weight | 4.0 lbs. | N/A | 11.79 lbs. | N/A |
| Warranty | 3-Year Limited | 3-Year Limited | 3-Year Limited Product*** 2-Year Limited Battery*** | 4-Year Limited |

*Maximum initial battery voltage (measured without workload) is 48-volts. Nominal voltage is 43.

**Run time, charge time and output capacity may be affected by conditions.

***Visit www.snapper.com for complete warranty details.

As rated by the manufacturer. Color and model may vary.



| | 80V Cordless Backpack Leaf Blower | 25cc Gas Leaf Blower | 26cc Gas Leaf Blower | 25cc Gas Leaf Blower / Vac |
|-----------------------|--|---|-----------------------------------|--|
| Menards® SKU | 267-3104 | 267-4701 | 267-4714 | 267-4710 |
| Model | 2400594ME | B215 | PLB26 | PPBV25 |
| Motor / Engine | 80V Brushless Motor | 25cc, 2-Cycle Engine | 26cc 2-Cycle Engine | 25cc 2-Cycle Engine |
| MPH / CFM | 145 MPH / 580 CFM | 200 MPG / 430 CFM | 190 MPH / 430 CFM | 230 MPH / 680 CFM |
| Capacity | N/A | N/A | N/A | 16:1 Mulch Ratio |
| Impeller | N/A | Plastic | Dedicated Blower | Plastic Impeller |
| Speed Control | Variable Speed Trigger, 3-Speed Settings | Variable | Variable Speed Trigger | Variable Speed Trigger |
| Features | Powerful performance – 145 MPH / 580 CFM powered by brushless motor. Comfortable shoulder straps distribute weight evenly during use. Variable speed trigger, 3-speed settings. Up to 30 minute runtime with included 2.0AH battery fully charged. Battery charges in 30 minutes with Rapid Charger. | Easy 3-step starting; prime, choke, pull; easy start technology for simpler pull starts; variable speed throttle with cruise control for greater control; includes extended nozzle with integrated scraper, 2-cycle oil | Easy-to-start, lightweight blower | Powerful 680 MPH blowing capability with a 16:1 mulch reduction ratio; vac kit included; soft touch handle |
| Weight | N/A | 10–12 lbs. | 9.5 lbs. | 9.5 lbs. |
| Warranty | 4-Year Limited | 2-Year Limited | 1-Year Limited | 2-Year Limited |

As rated by the manufacturer. Color and model may vary.

¹ Debris reduction varies with material type and its condition

LEAF BLOWERS



Electric



Battery



Gas

CRAFTSMAN®

POULANPRO

SOUTHLAND®



**27cc Gas
Leaf Blower / Vac / Mulcher**

**48cc Gas Backpack
Leaf Blower**

**163cc Gas Walk Behind
Leaf Blower**

| | | | |
|-----------------------|---|--|--|
| Menards® SKU | 267-4702 | 267-4713 | 267-1818 |
| Model | BV225 | PR48BT | SWB163150E |
| Motor / Engine | Full-Crank, 27cc, 2-Cycle Engine | Full-Crank, 48cc 2-Cycle Engine | 163cc 4-Cycle Engine |
| MPH / CFM | 205 MPH / 450 CFM | 200 MPH / 475 CFM | 150 MPH / 1200 CFM |
| Capacity | Vacuum Bag Capacity: 1.5 bushel | N/A | N/A |
| Impeller | Plastic | N/A | Steel |
| Speed Control | Variable | Variable Speed Trigger with Cruise Control | N/A |
| Features | Easy start technology for simpler pull starts; variable speed throttle with cruise control for greater control; includes vacuum kit with 1.5 bushel capacity bag for collecting leaves and debris with 16:1 debris reduction ratio, 2-cycle oil | Ergonomic shoulder harness full crank 1.5L fuel tank | Steel fan and fan housing for long life and durability; more air volume than backpack blowers; fan balanced for low vibration and long life; 12" high solid rear wheels & 6" swivel front wheel; side discharge chute with 3 position adjustable air flow outlet level, + 15° (up), - 15° (down); front flow outlet attachment included. |
| Weight | 9.885 lbs. | 19.8 lbs. | Walk behind blower-not carried |
| Warranty | 2-Year Limited | 2-Year Limited | 2-Year Limited |

As rated by the manufacturer. Color and model may vary.



CHAINSAWS





WHAT ABOUT CUTTING?

If you are cutting tree limbs, pruning and other on-ground cutting, look for 10" to 16" bar lengths. If you will be cutting logs and smaller trees, consider a 16" to 20" model.

CHOOSING A CHAINSAW

Electric

Choose a chainsaw with an electric engine for smaller jobs that are fairly close to a power source. They are lightweight, durable and produce no emissions.

Gas Powered

Chainsaws with gas-powered engines deliver more power to get bigger jobs done quickly, with the added mobility to work unconstrained by power cords.

What About Bar Length?

A good rule of thumb is that the bar length should be longer than the diameter of what you intend to cut.

- 10" to 12" bars are ideal for occasional light duty use and are easy to handle.
- 14" to 16" bars are great for moderate use on small to medium tree limbs and for on-ground cutting.
- 18" to 20" bars are best for frequent cutting of larger tree limbs and logs.



Chainsaws

Steel bucking teeth for optimum cutting performance.



Log Splitters

Offer the flexibility of vertical or horizontal operation.

CHAINSaws



Electric



Battery



Gas

WORX



REMINGTON



WORX



OREGON



**10" 8 AMP Corded
Chainsaw / Pole Saw Combo**

**10" 8 AMP Corded
Chainsaw / Pole Saw Combo**

**14" 8 AMP Corded
Chainsaw**

**16" 12 AMP Corded
Chainsaw**

Menards® SKU

267-4794

267-4789

239-1522

239-1558

Model

WG309

RM1035P

WG305

CS1200

Motor / Engine

8 AMP Electric, Corded

8 AMP Electric, Corded

8 AMP Electric, Corded

12 AMP Electric, Corded

Run Time (min)

N/A

N/A

N/A

N/A

Bar Length

10"

10"

14"

16"

Chain

3/8" x .05"

3/8" x .05"

3/8" x .05"

3/8" x .050"

Oil Pump

Automatic

N/A

Automatic

Automatic

Oil / Fuel Tank Capacity

4.0 oz.

N/A

4.0 oz.

3.4 fl. oz.

Case / Shoulder Strap

N/A

N/A

N/A

Not Included

Warranty

3-Year Limited

2-Year Limited

3-Year Limited

2-Year Limited

Replacement Parts

Chain

S40 / 239-1409

S40 / 239-1409

S52 / 239-1419

S56 / 239-1428

Bar / Chain Combo

N/A

N/A

27856 – 239-1446

27857 – 239-1449

Battery / Charger

N/A

N/A

N/A

N/A

Oil

N/A

N/A

N/A

54-026

greenworks®

greenworks®

MASTERFORCE®
BRUSHLESSMASTERFORCE®
BRUSHLESS**18" 14.5 AMP
Corded Chainsaw****8" 40V
Pole Saw****10" 80V
Pole Saw****18" 80V Brushless
Chainsaw**

| | | | | |
|--------------------------|------------------|---------------------------|---------------------------|----------------------------|
| Menards® SKU | 239-1554 | 239-1525 | 239-1524 | 239-1523 |
| Model | 20332 | 1405002ME | 1400094ME | 2000094ME |
| Motor / Engine | 14.5AMP | 40V Motor | 80V Brushless Motor | 80V Brushless Motor |
| Run Time (min) | N/A | Up to 50 Cuts of 4x4 Wood | Up to 80 Cuts of 4x4 Wood | Up to 150 Cuts of 4x4 Wood |
| Bar Length | 18" | 8" | 10" | 18" |
| Chain | 3/8" x .05" | 3/8" x .05" | 1/4" x .05" | 3/8" x .050" |
| Oil Pump | Automatic | Automatic | Automatic | Automatic |
| Oil / Fuel Tank Capacity | 5.1 fl. oz. | 2.7 fl. oz. | 2.7 fl. oz. | 2.7 fl. oz. |
| Case / Shoulder Strap | Not Included | Not Included | Shoulder Strap Included | Not Included |
| Warranty | 3-Year Limited | 3-Year Limited | 4-Year Limited | 4-Year Limited |
| Replacement Parts | | | | |
| Chain | S62 / 239-1438 | S33 | A58 | S62 / 239-1438 |
| Bar / Chain Combo | 39272 – 239-1452 | 29062 (Greenworks Bar) | N/A | 39272 – 239-1452 |
| Battery / Charger | N/A | 267-3317 / 267-3311 | 267-3313 / 267-3314 | 267-3313 / 267-3314 |
| Oil | GWBCO | GWBCO | GWBCO | GWBCO |

CHAINSaws



Electric



Battery



Gas

CRAFTSMAN®

POULAN®

Jonsered®

POULAN®



**8" 25cc
Gas Pole Saw**

**14" 33cc
Gas Chainsaw**

**14" 38cc
Gas Chainsaw**

**16" 38cc
Gas Chainsaw**

Menards® SKU

239-1527

239-1608

239-1673

239-1609

Model

P210

PL3314

CS2238

PL3816

Motor / Engine

25cc 2-Cycle Engine

33cc 2-Cycle Engine

38cc 2-Cycle Engine

38cc 2-Cycle Engine

Run Time (min)

N/A

N/A

N/A

N/A

Bar Length

8"

14"

14"

16"

Chain

3/8" x .050"

3/8" x .050"

3/8" x .050"

3/8" x .050"

Oil Pump

Automatic

Automatic

Automatic

Automatic

Oil / Fuel Tank Capacity

N/A

7.7 / 12.6 fl. oz.

6.7 / 10.1 fl. oz.

7.7 / 12.6 fl. oz.

Case / Shoulder Strap

Not Included

Not Included

Not Included

Not Included

Warranty

2-Year Limited

1-Year Limited

2-Year Limited

1-Year Limited

Replacement Parts

Chain

S33

S52 / 239-1419

S52 / 239-1419

S56 / 239-1428

Bar / Chain Combo

N/A

27856 – 239-1446

27856 – 239-1446

27857 – 239-1449

Spark Plug

49MA2SPP793

N/A

N/A

N/A

Oil

490-000-0060

50:1 Fuel to Oil

50:1 Fuel to Oil

50:1 Fuel to Oil

CRAFTSMAN®**POULANPRO****CRAFTSMAN®****Jonsered®****16" 42cc
Gas Chainsaw****18" 42cc
Gas Chainsaw****18" 42cc
Gas Chainsaw****18" 45cc
Gas Chainsaw**

| | | | | |
|---------------------------------|---------------------|---------------------|---------------------|---------------------|
| Menards® SKU | 239-1531 | 239-1619 | 239-1532 | 239-1675 |
| Model | S160 | PR4218 | S205 | CS2245 |
| Motor / Engine | 42cc 2-Cycle Engine | 42cc 2-Cycle Engine | 42cc 2-Cycle Engine | 45cc 2-Cycle Engine |
| Run Time (min) | N/A | N/A | N/A | N/A |
| Bar Length | 16" | 18" | 18" | 18" |
| Chain | 3/8" x .050" | 3/8" x .050" | 3/8" x .050" | 13/40" x .050" |
| Oil Pump | Automatic | Automatic | Automatic | Automatic |
| Oil / Fuel Tank Capacity | 7.7 / 12.6 fl. oz. | 6.7 / 11.8 fl. oz. | 7.7 / 12.6 fl. oz. | 8.7 / 15.2 fl. oz. |
| Case / Shoulder Strap | Included | Included | Included | Not Included |
| Warranty | 2-Year Limited | 2-Year Limited | 2-Year Limited | 2-Year Limited |
| Replacement Parts | | | | |
| Chain | S56 / 239-1428 | S62 / 239-1438 | S62 / 239-1438 | H72 / 239-1439 |
| Bar / Chain Combo | 27857 – 239-1449 | 39272 – 239-1452 | 39272 – 239-1452 | 180PXBK095 |
| Spark Plug | 49MA2SPP793 | N/A | 49MA2SPP793 | N/A |
| Oil | 40:1 Fuel to Oil | 50:1 Fuel to Oil | 40:1 Fuel to Oil | 50:1 Fuel to Oil |

CHAINSaws



Electric



Battery



Gas

POULANPRO

Jonsered®



20" 50cc
Gas Chainsaw

20" 50cc
Gas Chainsaw

| | | |
|--------------------------|----------------------------------|--|
| Menards® SKU | 239-1618 | 239-1676 |
| Model | PR5020 | CS2250 |
| Motor / Engine | 50cc 2-Cycle Engine | 50cc 2-Cycle Engine |
| Run Time (min) | N/A | N/A |
| Bar Length | 20" | 20" |
| Chain | 3/8" x .050" | 3/8" x .050" |
| Oil Pump | Automatic | Automatic |
| Oil / Fuel Tank Capacity | 9.9 / 14.3 fl. oz. | 8.7 / 15.2 fl. oz. |
| Case / Shoulder Strap | Included | Not Included |
| Warranty | 2-Year Limited | 2-Year Limited |
| Replacement Parts | | |
| Chain for Original Bar | D70 / 239-1440 or E70 / 239-1342 | M80 / 2391350 |
| Bar / Chain Combo | *584818 (D72 Chain) | *200TXLBK095 Bar Only Use with M78 / 239-1344 |
| Oil | 50:1 Fuel to Oil | 50:1 Fuel to Oil |

*Drive length count on replacement combo or chain differs from original OEM part.
As rated by the manufacturer. Color and model may vary.



PRESSURE WASHERS





LIGHT, MEDIUM, OR HEAVY-DUTY

Choose a light-duty pressure washer to clean cars and trucks, patio furniture, grills and sidewalks. Medium-duty pressure washers do those things plus fencing, decks, patios, garage floors, and driveways. While too strong to use on cars and trucks, heavy duty-pressure washers work on everything else. They also handle siding and second stories, and prepare surfaces for painting.

CHOOSING THE PRESSURE WASHER THAT MEETS YOUR NEEDS.

Engines

How much power do you need for the job? Most pressure washers are equipped with engines that have the right amount of power based on what the unit is intended to do. The engine selected will provide enough power to blast away the dirt, grime and anything else it is designed to remove.

Gas vs Electric

How far do you need to go? Gas-powered pressure washers deliver unbeatable cleaning performance, flexibility and durability, with the freedom to clean everywhere without cords to hold it back.

PSI and GPM

There are two different measurements for power in pressure washers. Both are important for cleaning. The higher both numbers are, the better it is at cleaning and blasting away dirt.

PSI is a measure of pounds per square inch at the output or the force the pressure washer creates.

GPM is the amount or flow of water being delivered to the sprayer. It is short for gallons per minute and gives you the power to break down dirt and wash it away.



OHV Engine

Runs longer, quieter and more efficiently than other engines.



Quick-Connect Spray Tips

Switch easily between a variety of spray patterns for every job.



Axial Cam Pump

Designed to be smooth starting and hassle-free with no need to change or add oil to the pump.

PRESSURE WASHERS

L Light-Duty

M Medium-Duty









H Heavy-Duty

CRAFTSMAN®

CRAFTSMAN®

CRAFTSMAN®

SUNJOE®

| |  L  |  L  |  L  |  L  |
|-----------------------|---|---|---|---|
| | 1600 MAX* PSI Corded Pressure Washer | 1800 MAX* PSI Corded Pressure Washer | 1900 MAX* PSI Corded Pressure Washer | 2050 MAX* PSI Elite Series Corded Pressure Washer |
| Menards® SKU | 261-1639 | 261-1640 | 261-1641 | 261-1660 |
| Model | CMXTPAV1600 | CMXTPAV1800 | CMXTPAV1900 | SPX2598-ELT |
| Motor / Engine | Durable 12 AMP | Durable 13 AMP | Durable 13 AMP | Durable 13 AMP |
| PSI / GPM | 1600 MAX* PSI / 1.2 MAX* GPM | 1800 MAX* PSI / 1.2 MAX* GPM | 1900 MAX* PSI / 1.2 MAX* GPM | 2050 MAX* PSI / 1.65 MAX* GPM |
| Pump | Aluminum Wobble Plate Pump | Aluminum Wobble Plate Pump | Aluminum Wobble Plate Pump | Aluminum Wobble Plate Pump |
| Spray Nozzles | Adjustable Spray Wand / High-Pressure Foam Cannon | Adjustable Spray Wand / Rotary Lance / High-Pressure Foam Cannon | 4 Quick-Connect Nozzles (0°, 15°, 25°, 40°) / High-Pressure Foam Cannon | 4 Quick-Connect Nozzles (0°, 15°, 25° + Bonus Turbo Nozzle) |
| Hose Length | 20' | 20' | 20' | 20' |
| Detergent | High-Pressure Foamer | High-Pressure Foamer | High-Pressure Foamer | 33.8 oz Foamer Cannon |
| Wheels | No | 6" Never-Go-Flat | 6" Never-Go-Flat | 6" Never-Go-Flat |
| Dimensions | 12.8" L x 8.3" W x 18.5" H | 14.9" L x 12.7" W x 32.3" H | 14.9" L x 12.7" W x 32.3" H | 10" L x 12" W x 30" H |
| Warranty | 2-Year Limited** | 2-Year Limited** | 2-Year Limited** | 2-Year Full |

*Per PWMA PW101-2010

**Visit www.CRAFTSMAN.com for complete warranty details.

As rated by the manufacturer. Color and model may vary.


SUNJOE®

**2250 MAX* PSI Elite Series
Corded Pressure Washer**
BRIGGS & STRATTON®

**2200 MAX* PSI Corded
Pressure Washer**
MASTERFORCE®

**2200 MAX* PSI Wall Mount
Capable Corded Pressure Washer**
WORX®

**320 MAX* PSI 20V Cordless
HYDROSHOT™ Power Cleaner**

| Menards® SKU | 261-1661 | 261-1625 | 261-1654 | 261-9306 |
|----------------|---|---|--|---|
| Model | SPX4003-ELT | 020700 | MF2200 | WG629 |
| Motor / Engine | Durable 14.5 AMP | Brushless Induction Motor | Brushless Induction Motor | 20V Lithium-Ion Battery |
| PSI / GPM | 2250 MAX* PSI / 1.65 MAX* GPM | 2200 MAX* PSI / 1.2 MAX* GPM | 2200 MAX* PSI / 1.2 MAX* GPM | 320 MAX* PSI / 0.5 GPM |
| Pump | Aluminum Wobble Plate Pump | Axial Cam | Axial Cam | Axial Cam |
| Spray Nozzles | Quick-Connect Professional Tip Set (0°, 15°, 25°, 40° + Soap) | 4 Quick-Connect Nozzles 15°, 40°, Turbo, Foamer | 4 Quick-Connect Nozzles 0°, 15°, 25°, Soap | 4 Quick-Connect Nozzles 0°, 15°, 25°, 40° and Shower |
| Hose Length | 20' | 25' | 25' | 20' |
| Detergent | 54.1 oz Onboard Detergent Tank | Detergent Foamer Nozzle & Siphon Hose | Detergent Tank & High-Pressure Foamer Bottle | 13.5 oz Detergent Container Attachment (WA4036 - Sold Separately) |
| Wheels | 8" Never-Go-Flat | 9" Never-Go-Flat | 8" Never-Go-Flat | N / A – Handheld Device |
| Dimensions | 21.2" L x 19.3" W x 36.6" H | 16.9" L x 15.5" W x 24" H | 14" L x 11.2" W x 4.8" H | 37.25" L x 2.25" W x 8" H |
| Warranty | 2-Year Full | 1-Year Limited** | 3-Year Limited** | 3-Year Limited |

*Per PWMA PW101-2010

**Visit www.briggsandstratton.com for complete warranty details.

As rated by the manufacturer. Color and model may vary.

PRESSURE WASHERS

L Light-Duty

M Medium-Duty

H Heavy-Duty

MASTERFORCE®



CRAFTSMAN®



GENERAC®



SNAPPER®



**400 MAX* PSI 20V Cordless
Power Cleaner (Tool-Only)**

**2800 MAX* PSI Gas
Pressure Washer**

**2900 MAX* PSI Gas
Pressure Washer**

**3000 MAX* PSI Gas
Pressure Washer**

| Menards® SKU | 261-9307 | 261-1644 | 261-1651 | 261-1657 |
|----------------|---|--|---|---|
| Model | MFMJ250 | 020788 | 7954 | 020787 |
| Motor / Engine | 20V Lithium-Ion Battery | 163cc Briggs & Stratton 725 EXi Series™ | 196cc Generac® OHV | 160cc Honda® GCV160 |
| PSI / GPM | 400 MAX* PSI / 0.8 GPM | 2800 MAX* PSI / 2.3 MAX* GPM | 2900 MAX* PSI / 2.4 MAX* GPM | 3000 MAX* PSI / 2.3 MAX* GPM |
| Pump | Axial Cam | Maintenance-Free Axial Cam with Easy Start™ Technology | Axial Cam | Axial Cam |
| Spray Nozzles | 4 Quick-Connect Nozzles 0°, 20°, 60° and Turbo | 4 Quick-Connect Nozzles (0°, 15°, 40°, Soap) | 4 Quick-Connect Nozzles (0°, 15°, 40°, Soap) | 5 Quick-Connect Nozzles (0°, 15°, 25°, 40°, Soap) |
| Hose Length | 13' | 25' | 25' | 25' |
| Detergent | 15 oz High-Pressure Foamer | Direct From Concentrate System & Siphon Hose | Ergonomic Gun On-Board | Chemical Tank |
| Wheels | N / A – Handheld Device | 10" Never-Go-Flat | 10" Never-Go-Flat | 10" Never-Go-Flat |
| Dimensions | 37.25" L x 2.25" W x 8" H | 22" L x 18.5" W x 39" H | 24.4" L x 18.9" W x 35.5" H | 30" L x 19" W x 40" H |
| Warranty | 3-Year Limited | 3-Year Limited Frame**, 2-Year Limited Engine & Equipment** | 2-Year Limited | 3-Year Limited Frame***, 2-Year Limited Engine & Equipment** |

*Per PWMA PW101-2010

**Visit www.CRAFTSMAN.com for complete warranty details.

***Visit www.snapper.com for complete warranty details.

As rated by the manufacturer. Color and model may vary.


GENERAC®

**3100 MAX* PSI Speed Wash
Gas Pressure Washer**
GENERAC®

**2100-3100 MAX* PSI Electric One
Start Gas Pressure Washer**
BRUTE®

**3100 MAX* PSI Gas
Pressure Washer**
SNAPPER®

**3400 MAX* PSI Gas
Pressure Washer**

| | Menards® SKU | 261-1647 | 261-1628 | 261-1387 | 261-1658 |
|--|----------------|---|---|--|---|
| | Model | 7955 | 7132 | 020743 | 020785 |
| | Motor / Engine | 196cc Generac® OHV | 173cc Generac® OHV | 187cc Honda® GC190 | 208cc CR950 Briggs & Stratton® |
| | PSI / GPM | 3100 PSI / 2.4 GPM | 2100-3100 PSI / 2.5 GPM | 3100 PSI / 2.7 MAX* GPM | 3400 MAX* PSI / 2.8 MAX* GPM |
| | Pump | Axial Cam | Axial Cam | Maintenance-Free Axial Cam with Easy Start™ Technology | Axial Cam |
| | Spray Nozzles | 4 Quick-Connect Nozzles 0°, 25°, 40°, Soap | 4 Quick-Connect Nozzles 0°, 25°, 40°, Soap | 4 Quick-Connect Nozzles (0°, 15°, 40°, Soap) | 5 Quick-Connect Nozzles (0°, 15°, 25°, 40°, Soap) |
| | Hose Length | 25' | 25' | 30' | 30' |
| | Detergent | Tank On-Board | Tank On-Board | Siphon Hose | Siphon Hose |
| | Wheels | 10" Never-Go-Flat | 10" Never-Go-Flat | 10" Pneumatic | 10" Pneumatic |
| | Dimensions | 24.2" L x 18.9" W x 35.5" H | 24.4" L x 19" W x 35.5" H | 25.5" L x 21.5" W x 31" H | 32" L x 22" W x 31" H |
| | Warranty | 3-Year Limited | 2-Year Limited | 2-Year Limited*** | 3-Year Limited Frame**, 2-Year Limited Engine & Equipment** |

*Per PWMA PW101-2010

**Visit www.snapper.com for complete warranty details.

***Visit www.brutepower.com for complete warranty details.

As rated by the manufacturer. Color and model may vary.

GENERATORS





PORTABLE OR HOME STANDBY?

Portable:

- Temporary backup power system
- No generator install needed
- Manual Starting
- Fuel Type: Gasoline refueling needed

Standby:

- Permanent backup power system
- Certified dealer or licensed electrician required for generator install
- Automatically starts when power goes out
- Fuel: Liquid Propane or natural gas line, no refueling needed

CHOOSING THE RIGHT GENERATOR FOR YOUR HOME

Standby or Portable?

Consider wattage and power when choosing the type of generator that fits your needs.

Understanding Running / Starting Watts

There are two basic power measurements for generators: starting watts and continuous or running watts. Starting wattage is required for appliances at startup or when they are running at their highest levels of power consumption. Continuous power is the wattage required for the operation of those appliances under normal load. Both are measured in wattage.

Run Time

Generators will call out how much run time they can get at 25% or 50% load. This represents about how much time they will run with a full fuel tank, using that percentage of their total power. If you think you will need more run time, or if you are using your generator for emergency situations where you cannot predict how long you will need it to run for, consider purchasing one with a larger tank.

Standby Generators

These generators typically run between 7,000 – 22,000 watts to offer 24 / 7 blackout protection. They automatically provide power to your home until the outage is over. Standby generators are professionally installed and draw their fuel supply from an existing line of natural gas or propane.

Portable Generators

Portable generators can be used to supply limited emergency storm power or power leisure activities like camping and tailgating. It is important to consider wattage, run time, size and mobility when choosing which portable generator is right for you.

Inverter Generators

Inverter generators are ideal for tailgating, camping, boating or RVing. These portable generators are smaller in wattage capabilities but are desirable for their clean power, quietness, efficiency and size.

GENERATORS

GENERAC®



BRUTE®



| | GP2200i Inverter Generator | P2200 PowerSmart Series™ Inverter Generator | P3000 PowerSmart Series™ Inverter Generator | 3500 W Portable Generator |
|----------------------------------|---|---|--|---|
| Menards® SKU | 240-1207 | 240-1199 | 240-1197 | 240-1100 |
| Model | 7117 | 030651 | 030545 | 030634 |
| Engine | 80cc Generac® OHV | 111cc OHV | 171cc OHV | 196cc OHV Briggs & Stratton® Powerbuilt™ Series |
| Running / Starting Watts | 1,700 / 2,200 | 1,700 ¹ / 2,200 ² | 2,600 ¹ / 3,000 ² | 3,500 ¹ / 5,250 ² |
| Starting Method | Pull | Pull | Pull | Pull |
| Outlet Configuration | (1) 1.5A 5VDC USB Outlet (1) 120V, 20A 5-20R Duplex Outlet | (2) 120V-20A (1) 12V-5A DC Accessory (1) Parallel Connector Port (1) USB Adapter | (4) 120V-20A (1) 12V-5A DC (1) 120V-30A Locking (1) Parallel Connector Port (1) USB Port | (4) 120V Household Outlets, (1) 120V-30A RV |
| Fuel Tank Type & Size | Plastic / 1.2 gallon | Metal, 1 gallon | Metal, 1.5 gallon with Gauge | Metal, 3 gallon with Gauge |
| Run Time | 10.75 Hours at 25% Load | 8 Hours at 25% Load | 10 Hours at 25% Load | 8 Hours at 50% Load |
| Product Dimensions | 19.7"L x 11.4"W x 17.9"H | 21"L x 12.5"W x 17.4"H | 26"L x 14"W x 21"H | 24"L x 18.5"W x 19"H |
| Warranty | 2-Year Limited Residential 1-Year Limited Commercial | 2-Year Limited Residential ³ 1-Year Limited Commercial ³ | 2-Year Limited Residential ³ 1-Year Limited Commercial ³ | 2-Year Limited Residential ⁴ 1-Year Limited Commercial ⁴ |
| Optional Accessories | GP2200i Parallel Kit #7118-0 | Parallel Kit #6278 – SKU 240-1198 | Parallel Kit #6278 – SKU 240-1198 | N/A |

As rated by the manufacturer. Color and model may vary.

¹ Per ANSI / PGMA G300-2015

² Starting Watts-This generator is rated in accordance with Briggs & Stratton standard 628K.

³ See operator's manual or www.briggsandstratton.com for complete warranty details.

⁴ See operator's manual or www.brutepower.com for complete warranty details.

GENERAC®
**3300W
Portable Generator**
CRAFTSMAN®
CO DETECTION
 CARBON MONOXIDE
 AUTO SHUT OFF

**5750W
Portable Generator**

**7000W¹
Portable Generator**
GENERAC®
**RS8000E
Portable Generator**

| | 3300W Portable Generator | 5750W Portable Generator | 7000W¹ Portable Generator | RS8000E Portable Generator |
|----------------------------------|--|---|---|---|
| Menards® SKU | 240-1075 | 240-1227 | 240-1228 | 240-1079 |
| Model | 6431 | 030790 | 030740 | G0079510 |
| Engine | 208cc Generac® OHV Engine with Low Oil Shutdown | 420cc Briggs & Stratton® OHV Engine | 420cc Briggs & Stratton® OHV Engine | 420cc Generac® OHV Engine with Low Oil Shutdown |
| Running / Starting Watts | 3,300 / 3,750 | 5,750 ¹ / 7,200 ² | 7,000 ¹ / 8,750 ² | 8,000 / 10,000 |
| Starting Method | Recoil | Pull | Electric / Recoil | Electric / Pull |
| Outlet Configuration | (2) 120V-20A GFCI 5-20R Duplex, (1) 120 / 240V-20A L14-20R Twist-Lock, 120 / 240V-20A to 120V-30A RV Adaptor (Supplied Loose) | (4) 120V-20A 5-20R GFCI (1) 120 / 240V-30A L14-30R TwistLock | (4) 120V-20A GFCI (1) 120 / 240V-30A Locking | (4) 120V-20A 5-20R GFCI (1) 120 / 240V-30A L14-30R TwistLock |
| Fuel Tank Type & Size | Steel, 3.5 gallon | Steel, 8.5 gallon with Gauge | Steel, 7.5 gallon | Steel, 7.5 gallon |
| Run Time | 10.25 Hours at 50% Load | 12 Hours at 50% Load | 9 Hours at 50% Load | 10.5 Hours at 50% Load |
| Product Dimensions | 24.2" L x 22.5" W x 21" H | 28" L x 25" W x 29" H | 30" L x 30" W x 29" H | 30" L x 27.1" W x 25.7" H |
| Warranty | 2-Year Limited | 2-Year Limited Engine & Equipment ⁴ 3-Year Limited Chassis ⁴ | 3-Year Limited | 3-Year Limited Residential – Enclosure 1-Year Limited Commercial – Enclosure |
| Optional Accessories | 6854 – 30A Homelink MTS | N/A | N/A | 6854 – 30A Homelink MTS |

As rated by the manufacturer. Color and model may vary.

¹ Per ANSI / PGMA G300-2015² Starting Watts-This generator is rated in accordance with Briggs & Stratton standard 628K.³ See operator's manual or www.briggsandstratton.com for complete warranty details.⁴ See operator's manual or www.CRAFTSMAN.com for complete warranty details.

GENERATORS



| | 12kW ² Generator with 200 AMP Transfer Switch | 13kW with Whole House TS Standby Generator | 16kW with Whole House TS Standby Generator | 20kW ² Generator with 200 AMP Transfer Switch |
|----------------------------|--|--|--|--|
| Menards® SKU | 240-0580 | 240-0674 | 240-0675 | 240-0678 |
| Model | 040626 | 7175 | 7178 | 040621 |
| Engine | 627cc, Vanguard® | 816cc, Generac® OHV | 816cc, Generac® OHV | 993 cc, Vanguard® |
| Rated Power | 12,000 watts (LPV) / 10,800 watts (NG) | 13,000 watts (LPG) / 13,000 watts (NG) | 16,000 watts (LPG) / 16,000 watts (NG) | 20,000 watts (LPV) / 18,000 watts (NG) |
| Voltage | 120V / 240V | 240 | 240 | 120V / 240V |
| LPG AMPs at 240V | 50 | 54.2 | 66.7 | 83.3 |
| LPG / LPV Fuel Consumption | 1.68 Gal / hr. at 50% load | 1.54 Gal / hr. at 50% load | 1.70 Gal / hr. at 50% load | 2.24 Gal / hr. at 50% load |
| NG AMPs at 240V | 45 | 54.2 | 66.7 | 75.5 |
| NG Fuel Consumption | 116.9 cubic ft. / hr. at 50% Load | 154 cubic ft. / hr. at 50% Load | 182 cubic ft. / hr. at 50% Load | 187 cubic ft. / hr. at 50% Load |
| Enclosure | Steel Frame | Aluminum | Aluminum | Steel Frame |
| Warranty | 5-Year Limited ¹ | 5-Year Limited | 5-Year Limited | 5-Year Limited ¹ |

¹ See operator's manual or briggsandstratton.com for complete warranty details.

² This generator is rated in accordance with UL (Underwriters Laboratories) 2200 (stationary engine generator assemblies) and CSA (Canadian Standards Association) standard C22.2 No.100-14 (motors and generators). As rated by the manufacturer. Color and model may vary.



**22kW with Whole House TS
Standby Generator**

| | |
|----------------------------|--|
| Menards® SKU | 240-0669 |
| Model | 70432 |
| Engine | 999cc, Generac® OHV |
| Rated Power | 22,000 watts (LPG) / 19,500 watts (NG) |
| Voltage | 240 |
| LPG AMPs at 240V | 91.7 |
| LPG / LPV Fuel Consumption | 2.53 Gal / hr. at 50% load |
| NG AMPs at 240V | 81.3 |
| NG Fuel Consumption | 228 cubic ft. / hr. at 50% Load |
| Enclosure | Aluminum |
| Warranty | 5-Year Limited |



**CONFIDENCE & COMFORT
DURING A POWER OUTAGE**

Standby power won't leave you in the dark.

Few scenarios for a family are met with as much universal frustration as waiting out a power outage in the dark. A power outage interrupts a family's daily routine and forces life to be put on pause until the power returns.

Standby generator systems prevent that. Period. Standby generator systems are designed to keep lights and home appliances powered in the event of a power outage—automatically. Best of all, they provide peace of mind that your family won't have to endure another headache-inducing power outage in the dark.

CHORE PERFORMERS



CHOOSING A LAWN EDGER

Buying a lawn edger could be a great decision, because if there is one single thing you can do to make your garden look sharp – it's edging your lawn and garden beds.

Q: How do I know which kind of lawn edger to choose?

If you are ready to purchase a lawn edger for your home, but are unsure of what type will suit you best, you need to ask yourself some important questions.

Q: How big is my yard?

Perhaps the most important consideration to take into account when looking for a new lawn edger is the size of your property. Typically, edgers are used along sidewalks, driveways and around the perimeters of flower beds and gardens.

If your property features numerous areas which must be edged with regularity, you will probably want to spend more money for a larger, more powerful machine that will take more of the effort out of the job for you.

If you have minimal edging to accomplish, you may be better off purchasing a smaller edger.

Q: Gas or electric?

Lawn edgers are available in gas or electrically-powered models. If you require power and speed, you should probably opt for a gas-powered unit.

If you have a smaller yard with minimal edging to do, you should probably choose an electric unit.

CHOOSING THE TILLER THAT MEETS YOUR NEEDS. UNDERSTANDING THE DIFFERENCE BETWEEN FRONT AND REAR TINE.

Front-Tine Tillers

Front-tine tillers have tines mounted in the front. The tines rotate in a forward direction, pulling the tiller through the dirt. The rear-mounted wheels provide the ability to transport the unit and help guide the machine. The depth stake prevents the unit from running away and gives the operator more control. The engine is placed over the tines, providing weight that helps the unit dig into the earth. These units are best for small gardens (less than 2,500 square feet) that have been previously cultivated.

Rear-Tine Tillers

Rear-tine tillers feature tines that are mounted behind the large drive wheels, with the engine mounted forward over the wheels. This provides the unit with better traction and balance. Rear-tine tillers operate more smoothly and are easier to handle than front-tine tillers, even in smaller areas. Rear-tine tillers are recommended for installing new gardens or maintaining gardens up to 10,000 square feet.



16" Tilling Width

Lets you tackle more ground in one pass.



Looped Handle

Provides easy, comfortable control.



Large Drive Wheels

Smoother, easier operation with better friction and balance.

POWERHEADS & AUGERS



Electric



Battery



Gas



| | 1-Man Earth Auger Powerhead | Dually 1-or 2-Man Earth Auger Powerhead | 2-Man Earth Auger Powerhead | 6" Earth Auger with Fishtail |
|-------------------|-----------------------------|---|---|------------------------------|
| Menards® SKU | 270-1909 | 270-1916 | 270-1927 | 270-1912 |
| Model | E43 | 10310 | 9800K | EA6F |
| Motor / Engine | 43cc Viper® Gas Engine | 52cc Viper Gas Engine | Powerhead 2-Man 4-Cycle XT775 Kohler® | N/A |
| Blade Length | N/A | N/A | N/A | N/A |
| Max RPM | 250 RPM | 285 RPM | 121 RPM | N/A |
| Weight | 22 lbs. | 24 lbs. | 52 lbs. | N/A |
| Gear Ratio | 30:1 | 30:1 | 30:1 | N/A |
| Features | N/A | N/A | N/A | 6" Diameter, 36" Length |
| Warranty | 5-Year Limited | 5-Year Limited | 5-Year Limited Product 2-Year Limited Engine | 5-Year Limited |
| Replacement Parts | | | | |
| Air Filter | 3004156 | 3004156 | 797301 (B&S part) | N/A |
| Spark Plug | 35906 | 35906 | 100005 (B&S part) | N/A |
| Blade | N/A | N/A | N/A | EB6 |
| Oil | 300400 | 300400 | 799876 (B&S part) | N/A |

As rated by the manufacturer. Color and model may vary.



| | 8" Earth Auger with Fishtail | 10" Earth Auger with Fishtail |
|-------------------|---------------------------------|----------------------------------|
| Menards® SKU | 270-1925 | 270-1926 |
| Model | EA8F | EA10F |
| Motor / Engine | N/A | N/A |
| Blade Length | N/A | N/A |
| Max RPM | N/A | N/A |
| Weight | N/A | N/A |
| Gear Ratio | N/A | N/A |
| Features | 8" Diameter, 36" Length | 10" Diameter, 36" Length |
| Warranty | 5-Year Limited | 5-Year Limited |
| Replacement Parts | | |
| Blade | EB8 | EB10 |



As rated by the manufacturer. Color and model may vary.

CULTIVATORS / TILLERS



Electric



Battery



Gas

EARTHWISE



**10 AMP
Corded Tiller**

EARTHWISE



**13.5 AMP
Corded Tiller**

**BLACK+
DECKER**



**20V Lithium-Ion
Cordless Cultivator**

MASTERFORCE[®]
BRUSHLESS



**10" 80V
Cordless Tiller**

| | | | | |
|--------------------------|---------------------|----------------------|---------------------|---------------------------|
| Menards [®] SKU | 270-2453 | 270-2444 | 270-2451 | 270-2454 |
| Model | TC70010 | TC70016 | LGC120 | 2800194ME |
| Motor / Engine | 10 AMP Electric | 13.5 AMP Electric | 20V Lithium Battery | 80V Brushless Motor |
| Front / Rear Tine | Front | Front | Front | Front |
| Tilling Width | Adjustable 7" – 11" | Adjustable 11" – 16" | 7" | Adjustable 6" – 10" |
| Tine Diameter | 7.5" | 7.5" | 4" | 5" |
| Wheels | Adjustable 5" | Adjustable 5" | N/A | 8" |
| Handle | Ergonomic Cushioned | Ergonomic Cushioned | Adjustable Side | Ergonomic Cushioned |
| Warranty | 2-Year Limited | 2-Year Limited | 2-Year Limited | 4-Year Limited |
| Replacement Parts | | | | |
| Tines | RTC700SET | RTC70016SET | N/A | 29453 |
| Battery | N/A | N/A | 20V – 236-6532 | 267-3313 – 2.0 AH Battery |
| Charger | N/A | N/A | 236-6534 | 267-3314 – Rapid Charger |

As rated by the manufacturer. Color and model may vary.

| | | | | |
|--|---------------------------------------|---|--|--|
| <div></div> | <div>Mini Gas Cultivator</div> | <div>Versa Front Tine Gas Tiller</div> | <div>Badger Front Tine Gas Tiller</div> | <div>Victory Rear Tine Gas Tiller</div> |
|--|---------------------------------------|---|--|--|

| | | | | |
|-------------------|----------------------------------|----------------------------------|---|---|
| Menards® SKU | 270-1833 | 270-1801 | 270-1818 | 270-1819 |
| Model | 31452 | 20015 | 20908 | 29702 |
| Motor / Engine | Viper® 33cc | Viper® 99cc | Kohler® 149cc | 196cc Kohler® 4-Cycle |
| Front / Rear Tine | Front Tine | Front Tine | Front Tine | Rear Tine |
| Tilling Width | Adjustable Tine Width | Adjustable Tine Width | Adjustable Tine Width | 16" |
| Tine Diameter | 8" | 11", 16", 21" | 11", 16", 21" | 11" |
| Wheels | N/A | Airless, 8" | Swing Out Wheels | Airless, 13" x 5" |
| Handle | Bicycle Style with Comfort Grips | Bicycle Style with Comfort Grips | Bicycle Style with Comfort Grips | Loop Style Multi-Position |
| Warranty | 5-Year Limited | 5-Year Limited | Tiller 5-Year Limited Product Engine 2-Year Limited Engine | 5-Year Limited Product 2-Year Limited Engine |
| Replacement Parts | | | | |
| Tines | 4601, 4602, 4603, 4604 | 13904, 13905 | 13903, 13904, 13905 | 13903, 13904, 13905 |
| Belt | N/A | 20343 | 22633 | 22633 |
| Air Filter | 3004156 | 10236 | 595191 (B&S) | 595191 (B&S) |
| Spark Plug | 35906 | 26286 | 594056 (B&S) | 594056 (B&S) |
| Oil | 300400 | 301401 | SAE 10W30 | SAE 10W30 |

EDGERS, TILLERS AND LOG SPLITTERS



Electric



Battery



Gas



**12 AMP
Electric Edger**



Gas Edger

| | | |
|-------------------|--|---------------------------------|
| Menards® Sku | 267-2928 | 267-4903 |
| Model | LE750 | YF7302 |
| Motor / Engine | 12 AMP Electric Motor | 79cc 4-Stroke Gas Engine |
| Blade Length | 7-1/2" | 9" |
| Blade Speed | 4700 RPM | 4500 RPM |
| Features | Toolfree assembly is quick and hassle-free | Adjustable and Fold-able Handle |
| Warranty | 2-Year Limited | 2-Year Limited |
| Replacement Parts | | |
| Blade | 267-3037 (EB-007A) | 267-3038 |



Gas Edger

| | |
|-------------------|---|
| Menards® SKU | 270-1814 |
| Model | 25623 |
| Motor / Engine | Briggs & Stratton XR550 Professional Series™ 127cc Gas Engine |
| Blade Length | 8.75" |
| Blade Speed | 3750 RPM |
| Features | Convenient Tool Holder on Handlebars |
| Warranty | 2-Year Limited |
| Replacement Parts | |
| Belt | 24021 |
| Air Filter | 797258 (B&S) |
| Spark Plug | 270-4325 |


As rated by the manufacturer. Color and model may vary.
*All power levels are stated gross torque at 2600RPM per SAE J1940 as rated by Briggs & Stratton®


SOUTHLAND®
BRUTE®
BRUTE®


**6-Ton Electric
Log Splitter**
**22-Ton Gas
Log Splitter**
**30-Ton Gas
Log Splitter**

| | | | |
|-----------------------------|-----------------------------------|--|--|
| Menards® SKU | 270-1017 | 270-1003 | 270-1010 |
| Model | SELS60M | YTL-015-691 | YTL-014-441 |
| Motor / Engine | 1.75 HP Induction Motor, 3400 RPM | Briggs & Stratton CR950 Series, 208cc Gas Engine | Briggs & Stratton CR950 Series™ 208cc Gas Engine |
| Raw Force | 6-Ton | 22-Ton | 30-Ton |
| Maximum Log Length | 20.5" | 25" | 26" |
| Wedge | 5" Fixed | 7" Hardened Steel | 8" Hardened Steel |
| Cycle Time (Seconds) | 18 Seconds | 13 Seconds | 13 Seconds |
| Log Trays (Yes / No) | No | No | Yes |
| Wheels (in.) | 7" Solid Rubber | 16" | 16" |
| Oil Reservoir | 3.7 quarts. | 2.64 Gallons | 3.17 Gallons |
| Assembly | Minimal | Minimal | Minimal |
| Warranty | 2-Year Limited | 3-Year Workmanship 2-Year Engine 1-Year Hydraulics | 3-Year Workmanship 2-Year Engine 1-Year Hydraulics |

WALK BEHIND STRING TRIMMER & COMPACTORS

 Electric

 Battery

 Gas



22" Gas Walk Behind String Mower

| | |
|-------------------|--|
| Menards® SKU | 270-0911 |
| Model | BS1022H |
| Motor / Engine | 190cc Briggs and Stratton® 875EXi Engine |
| Cut Width | 22" |
| Handles | Foam Handle Grips |
| Line Size | 0.155" |
| Features | Cut or Mow-Grass, Brush or Trimming |
| Wheels | 14" Rear high Wheels |
| Warranty | 3-Year Limited |
| Replacement Parts | |
| Oil | SAE30 / Synthetic 5W30 |
| Air Filter | 5452K |
| Spark Plug | 270-4332 / 270-4432 |



Gas Plate Compactor

| | |
|-----------------------|---------------------|
| Menards® SKU | 240-0700 |
| Model | 56035M |
| Motor / Engine | 212cc, 4-Stroke OHV |
| Compacting Plate Size | 24" x 18" |
| Vibrations Per Minute | 5,400 |
| Compaction Force | 4,496 lbs. |
| Fuel Tank Capacity | 1 Gallons |
| Forward Travel | Up to 82 ft / min |
| Finish | Powder Coat |
| Meets EPA Regulations | Yes |
| Weight | 231 lbs. |
| Warranty | 1-Year Limited |



Earthquake®
GROUNDBREAKING POWER EQUIPMENT™



**Chipper
Shredder**

| | |
|------------------|----------------------|
| Menards® SKU | 270-3712 |
| Model | 30520 |
| Motor / Engine | 212cc Viper® 4-Cycle |
| Chipper Capacity | Up to 3" |
| Reduction | 20:1 |
| Wheels | 11" |
| Warranty | 5-Year Limited |



MENARDS®



1.800.544.6986
blackanddecker.com



1.800.526.6937
lawnboy.com



1.800.800.7310
remingtonpowertools.com



1.800.743.4115
briggsandstratton.com



1.866.384.8432
lawnmaster.com



1.800.317.7833
snapper.com



1.800.743.4115
brutepower.com



1.866.384.8432
lawnmaster.com



800.737.2112
matholdingsinc.com



1.888.331.4569
craftsman.com



1.866.917.4374
menards.com



1.866.766.9563
www.snowjoe.com



1.800.345.6007
getearthquake.com



1.888.909.6757
menards.com



1.888.384.9939
toro.com



1.800.633.1501
earthwisetools.com



1.800.223.5168
oregonproducts.com



1.800.232.1195
wenproducts.com



1.888.436.3722
generac.com



1.800.554.6723
poulan.com



1.866.354.9679
worx.com



1.888.909.6757
greenworkstools.com



1.800.849.1297
poulanpro.com



1.866.902.9690
yardforceusa.com



1.800.487.5951
jonsered.com



1.866.591.8921
pulsar-products.com



1.800.269.6215
yardmachines.com